

# Plastic Products :-

## Tuffline Layflat Discharge Hose :

- Hi-strength Terylene yarn and qualified PVC synthesis materials.
- Light weight, good flexibility, bright colour and smooth smearing layer.
- Flat roll and easy for take back, convenient for moving and nolimitation for length.
- Anti-hi pressure, corrosion resistance and ageing resistance.

Applied to the lines of the auxiliaries for agricultural tools against the drought, project, mining, environment protection, industry and so on, which is the most ideal liquid-transferred hi-pressure hose.

size	I.D.	0.2	0.3	0.4	0.6	0.8	1.0
(Inch)	(mm)	Mpa	Mpa	Mpa	Mpa	Mpa	Mpa
		Kg/m	Kg/m	Kg/m	Kg/m	Kg/m	Kg/m
1"	25+/-1.3	0.12	0.13	0.14	0.155	0.17	0.185
1-1/4"	31.8+/-1.3	0.14	0.15	0.175	0.195	0.21	0.23
1-1/2"	38.1+/-1.5	0.18	0.20	0.24	0.27	0.30	0.32
2"	50.3+/-2.0	0.24	0.30	0.35	0.375	0.39	0.42
2-1/2"	63.5+/-2.3	0.32	0.38	0.45	0.48	0.52	0.55
3"	76.2+/-2.3	0.38	0.47	0.57	0.63	0.69	
4"	101.6+/-2.5	0.52	0.58	0.72	0.80	0.90	
5"	127+/-2.8	0.75	0.85	0.95	1.10	1.20	
6"	152.4+/-3.0	0.90	1.05	1.20	1.40		
8"	203.2+/-3.5	1.45	1.55	1.70	1.90		

